

A107878




LEVEL

Report 2334

REMOVAL OF HYDROCARBON TASTE AND ODOR FROM
POTABLE WATER BY REPLACEABLE
CARBON-CONTAINING FILTER CARTRIDGES

by Elizabeth Radoski


August 1981



Approved for public release; distribution unlimited.

U.S. ARMY MOBILITY EQUIPMENT
RESEARCH AND DEVELOPMENT COMMAND
FORT BELVOIR, VIRGINIA

31 17 36



Destroy this report when it is no longer needed. Do not return it to the originator.

The citation in this report of trade names of commercially available products does not constitute official endorsement or approval of the use of such products.

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER 2334 2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
2.334 (4) - (4 / 0 ° /) 4. TITLE (and Subtitle)	S. TYPE OF REPORT & PERIOD COVERED
REMOVAL OF HYDROCARBON TASTE AND ODOR FROM POTABLE WATER BY REPLACEABLE	Final Technical Report
CARBON-CONTAINING FILTER CARTRIDGES	5. PERFORMING ORG REPORT NUMBER
7. AUTHOR(a)	8. CONTRACT OR GRANT NUMBER(*)
Elizabeth Radoski	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Petroleum & Environmental Tech Div; Energy & Water Res Lab:	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
U.S. Army Mobility Equipment Research and Development	Proj/Task:
Command; Fort Belvoir, Virginia 22060	1L162733AH20EW
11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE August 1981
U.S. Army Mobility Equipment Research and Development Command; Fort Belvoir, Virginia 22060	13. NUMBER OF PAGES
	23
14. MONITORING AGENCY NAME & ADDRESS(If different from Controlling Office)	15. SECURITY CLASS. (of this report)
,	Unclassified
	154. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)	<u> </u>
Approved for public release; distribution unlimited.	
Approved for public felease, distribution unlimited.	
17. DISTRIBUTION STATEMENT (of the abetract entered in Block 20, if different from	m Report)
18. SUPPLEMENTARY NOTES	
THE SUPPLIES IN THE SUPPLIES	
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)	
Filter	
Potable Water	
Palatability Water Treatment	j
Water Pollution	
20. ASTRACT (Continue on reverse side if recessary and identify by block number)	
This report covers an investigation conducted to evaluate the containing filter cartridges for the removal of hydrocarbon taste non-drinkable by diesel fuel contamination. The results of the st filter cartridges effectively remove diesel fuel from potable water I mg/I of fuel; POL tankers can be equipped with a simple housing filter cartridges for the conversion of cleaned POL tankers.	and odor from potable water made udy indicate: carbon-containing contaminated with the addition of ng containing replaceable carbon-
service.	
(A)	

DD FORM 1 M73 EDITION OF 1 HOV 65 IS OBSOLETE

UNCLASSIFIED

PREFACE

The investigation covered by this report was an evaluation of the Filterite cartridge C40P-W2-U-ECIU, a carbon-containing filter, for the removal of the hydrocarbon taste and odor from potable water contaminated with diesel fuel. Work covered by this report was conducted under Project/Task 1L162733AH20-EW, "Water and Wastewater Management/Investigate Cartridge Filters."

The investigation was conducted by personnel of the Petroleum and Environmental Technology Division, Energy & Water Resources Laboratory, US Army Mobility Equipment Research and Development Command (MERADCOM), Fort Belvoir, Virginia. The investigation was directed by Mr. Maurice Pressman, Project Engineer. Mr. Peder B. Pedersen. Engineering Technician, set up the equipment. Mrs. Elizabeth Radoski, Chemist, conducted the tests.

Acce	ssion For	
	GRA&I	
DIIC	TAB]
Unannounced		
Just	ification	
Ву		
Dist	ribution/	
Ava	ilability Code	s
	Avail and/or	
Dist	Special	1
1	1 1	ł
	1 1	1
u	1 1	ı



CONTENTS

Section	Title	Page
	PREFACE	iii
	ILLUSTRATIONS	iv
Ī	INTRODUCTION 1. Objective 2. Background	1
II	INVESTIGATION 3. Subject 4. Equipment 5. Procedure	2 2 2
Ш	RESULTS 6. Test Data	2
IV	DISCUSSION 7. Discussion	7
V	CONCLUSIONS 8. Conclusions	8
	APPENDIX DATA OF TESTING RESULTS	9

ILLUSTRATIONS

Figure	Title	Page	
1	Total System	3	
2	500-Gal Plastic Tank	4	
3.	30-Gal/min Electric Pump	5	
4.	Filterite Corporation Open Filter Housing Containing Eight 40-in. Filter Cartridges	6	
5	Army 5000-Gal POL Tanker with Filter Separation	7	

THE REMOVAL OF HYDROCARBON TASTE AND ODOR

FROM POTABLE WATER BY REPLACEABLE CARBON

CONTAINING FILTER CARTRIDGES

I. INTRODUCTION

- 1. Objective. The objective of this investigation was to determine the effectiveness of the Filterite Cartridge C40P-W2-U-ECIU, a replaceable carbon-containing filter, for the removal of hydrocarbon taste and odor from drinking water made undrinkable by diesel fuel contamination. Tests conducted were part of a test program evaluating POL tanker cleaning and water treatment procedures which would be required to convert POL tankers to potable water service in contingency operations.
- 2. Background. The investigation covered by this report was conducted as a followup to the study, entitled "Conversion of Army Fuel Tankers to Potable Water Service," conducted during the period July 1979 to August 1979 by Janet Hall, of the Petroleum and Environmental Technology Division, MERADCOM, The objective of the Hall investigation was to evaluate the adequacy of two cleaning methods for converting a 50MM-gallon petroleum tanker to potable water service. The Hall investigation was a joint effort conducted by the US Army Quartermaster School, ATSM-CD-M and the Petroleum and Environmental Technology Division, Energy and Water Resources Laboratory, MERADICOM. The investigation was conducted as part of the TRADOC Concept Evaluation Program. No. TRMS9CEP011. Two M857 series tankers were obtained through USATARADCOM, Warren, Michigan, These two semitrailer tanks, 5000-gal capacity each (an M967, bulk hauf model, and an M969, automotive fuel-dispensing model), had contained loads of diesel fuel and leaded mogas. The M967 bulk haul model semitrailer was cleaned with detergent (MIL-D-16791C Type 1) using TB ORD 1031 as guidance and steam cleaned in accordance with par. 52A(3) of TM5-700. The M969 (automotive refueler) model semitrailer was cleaned with a chemical solvent (25 gal of Product-Sol No. 913, an emulsified solvent/detergent mixture). Based on the data obtained during this investigation the following conclusions were drawn:
- a. Both cleaning procedures are acceptable for converting 5000-gal fuel tankers to potable water service.
- b. Even though chemical analysis indicated that the water stored in the tankers met the potable water standards of TB MED 229, the water acquired taste and odor which made it unpalatable.
- c. Water made unpalatable by traces of residual fuel can be made palatable by passing it through granular activated earbon.

The investigation covered in this report was conducted to evaluate the effectiveness of the Filterite cartridge C40P-W2-U-ECIU, a commercially available carbon-containing filter for the removal of the hydrocarbon taste and odor from potable water contaminated with diesel fuel.

II. INVESTIGATION

- 3. Subject. During tests conducted in June 1979, it was demonstrated that even though POL tankers were vigorously cleaned by detergents or water-soluble petroleum solvents and thoroughly flushed with tap water, potable water stored in the tankers took on an objectionable hydrocarbon taste and odor which made the water unpalatable to a panel of tasters. Laboratory tests indicated that the taste and odor could be removed by passing the water through granular-activated carbon columns. The investigation covered by this report was conducted to assess the possibility of using filter cartridges containing carbon for the removal of taste and odor from fuel-contaminated water. The testing was done by Elizabeth Radoski during the period 25 Nov 80 to 5 Dec 80 at the Petroleum and Environmental Technology Division, Energy and Water Resources Laboratory, MERAD-COM (Figure 1). Samples were collected in styrofoam cups (Figures 1 and 4).
 - 4. Equipment. The following items of test equipment were used:
 - a. 500-gal plastic tank (Figure 2).
- b. 30-gal/min electric pump (Figure 3) manufactured by Gould, Inc.; Century Electronic Division; St. Louis, MO 63166.
- c. Filter housing containing eight 40-in, filter tubes (C40P-W2-U-ECIU) marketed by Filterite Corporation; Timonium, Maryland 21093 (Figure 4).
- 5. Procedure. The 500-gal tank was filled with tap water and contaminated with 1 mg/l of diesel fuel. The contaminated water was pumped through the filter housing equipped with the Filterite cartridges. The filter effluent was sampled at various intervals. The time of sampling, temperature of sample, and taste and odor observations were reported.

III. RESULTS

6. Test Data. The results obtained in the investigation of evaluating the Filterite cartridge C40P-W2-U-ECIU for removal of hydrocarbon taste and odor from potable water contaminated with diesel fuel are given in the Appendix.




Figure 1. Total system.




Figure 2. 500-Gal plastic tank.



Figure 3. 30-Gal/min electric pump.




Figure 4. Filterite Corporation open filter housing containing eight 40-in, filter cartridges,

IV. DISCUSSION

7. Discussion. Twenty 500-gal tank volumes of potable water contaminated with I mg/l diesel fuel were run through the filter unit. The test water had a strong hydrocarbon taste and odor. The filtered water was free of any objectionable taste or odor. The volume of test water processed through the same filter cartridges is equivalent to two 5000-gal tanker loads of water. The filters were still working effectively after passage of 10,000 gal of water. Breakthrough was not established for the Filterite cartridges because of limitations on the available water for testing due to an area drought condition. Results indicated that the carbon-bearing cartridges were effective for the removal of taste and odor caused by the addition of 1 mg/l of diesel fuel to the potable water.

The Army's 5000-gal POL tanker is equipped with a filter separator (Figure 5) as part of its dispensing system. A detailed examination of the tanker by the Engineering Division of the Energy & Water Resources Laboratory indicated that this filter separator could easily be removed and replaced by a simple housing containing the filter cartridges which were tested. This filter cartridge assembly could serve as an effective polishing filter for the removal of objectionable taste and odor from water dispensed from cleaned POL tankers.




Figure 5. Army 5000-gal POL tanker with filter separation.

V. CONCLUSIONS

8. Conclusions. It is concluded that:

- a. Carbon-bearing filter cartridges effectively removed diesel fuel from potable water contaminated with the addition of 1 mg/l of fuel.
- b. POL tankers can be equipped with a single housing containing carbonbearing filter cartridges for the conversion of cleaned tankers to potable water transport service.

APPENDIX

DATA OF TESTING RESULTS

Initial observation of contaminated water:

- Oil film visible on surface of water
- Strong diesel fuel odor
- Tasted like gasoline—taste remained on tongue for the day.

SAMPLE TIME	TEMP	COMMENTS
Tank No. 1		Date: 25 Nov 80
5 min 13 min 15 min	18° C 18° C 18° C	Radoski "No odor/No taste" Radoski "No odor/No taste" Radoski "No odor/No taste"
Tank No. 2		Date: 26 Nov 80
5 min 13 min 15 min	18° C 18° C 18° C	Radoski "No odor/No taste" Radoski "No odor/No taste" Hasle "No odor"
Tank No. 3		Date: 26 Nov 80
5 min 10 min 15 min	16° C 16° C 16° C	Radoski "No odor/No taste" Radoski "No odor/No taste" Radoski "No odor/No taste"
Tank No. 4		Date 26 Nov 80
5 min 10 min 15 min	14° C 14° C 14° C	Radoski "No odor/No taste" Radoski "No odor/No taste" Radoski "No odor/No taste"
Tank No. 5		Date: 2 Dec 80
5 min 10 min 15 min	19° C 19° C 19° C	Radoski "No odor/No taste" Radoski "No odor/No taste" Radoski "Potable Water"
Tank No. 6		Date: 2 Dec 80
5 min 10 min 15 min	14° C 14° C 14° C	Radoski "No taste/No odor" Radoski "No taste/No odor" Radoski "No taste/No odor"
Tank No. 7		Date: 2 Dec 80
5 min 10 min 15 min	16° C 16° C 16° C	Radoski "No taste/No odor" Radoski "No taste/No odor" Radoski "No taste/No odor"
Tank No. 8		Date: 2 Dec 80
5 min 10 min 15 min	14° C 14° C 14° C	Radoski "No taste/No odor" Radoski "No taste/No odor" Radoski "No taste/No odor"

SAMPLE TIME	TEMP	COMMENTS
Tank No. 9		Date: 3 Dec 80
5 min	16° C	Radoski "No taste/No odor"
10 min	16° C	Radoski "No taste/No odor"
15 min	16° C	Radoski "No taste/No odor"
Tank No. 10		Date: 3 Dec 80
5 min	14° C	Radoski "No taste/No odor"
10 min	14° C	Radoski "No taste/No odor"
15 min	14° (`	Radoski "No taste/No odor"
Tank No. 11		Date 3 Dec 80
5 min	16° C	Radoski "No taste/No odor"
10 min	16° C	Radoski "No taste/No odor"
15 min	16° C	Radoski "No taste/No odor"
Tank No. 12		Date: 3 Dec 80
5 min	16° €	Radoskí "No taste/No odor"
10 min	16° C	Radoski "No taste/No odor"
15 min	16° €	Eskelund "No taste/No odor"
Tank No. 13		Date: 4 Dec 80
5 min	14° (`	Radoski "No taste/No odor"
10 min	14° C	Radoski "No taste/No odor"
15 min	14° C	Radoski "No taste/No odor"
Tank No. 14		Date: 4 Dec 80
5 min	13° C	Radoski "No taste/No odor"
10 min	13° C	Radoski "No taste/No odor"
15 min	13° C	Davey "Drinkable"
Tank No. 15		Date: 4 Dec 80
5 min	13° C	Radoski "No taste/No odor"
10 min	13° C	Radoski "No taste/No odor"
15 min	13° C	Radoski "No taste/No odor"
Tank No. 16		Date: 4 Dec 80
5 min	14° C	Radoski "No taste/No odor"
10 min	14° C	Radoski "No taste/No odor"
15 min	14° C	Radoski "No taste/No odor"

a completime	TEMP	COMMENTS
SAMPLE TIME		Date: 5 Dec 80
Tank No. 17		
5 min 10 min 15 min	14° C 14° C 14° C	Radoski "No taste/No odor" Radoski "No taste/No odor" Radoski "No taste/No odor"
1.5 mm		Date: 5 Dec 80
Tank No. 18		Radoski "No taste/No odor"
5 min 10 min	13° C 13° C 13° C	Radoski "No taste/No odor" Radoski "No taste/No odor"
15 min		Date: 5 Dec 80
Tank No. 19		
5 min 10 min 15 min	12° C 12° C 12° C	Radoski "No taste/No odor" Radoski "No taste/No odor" Pressman "No taste/No odor"
(3 mm		Date: 5 Dec 80
Tank No. 20	, 20 C	Radoski "No taste/No odor"
5 min 10 min 15 min	12° C 12° C 12° C	Radoski "No taste/No odor" Eskelund "Good Potable Water"

DISTRIBUTION FOR MERADCOM REPORT 2334

No. Copies	Addressee	No. Copies	Addressee
	Department of Defense	1	Director US Army Materiel Systems
1	Director, Technical Information Defense Advanced Research Projects Agency 1400 Wilson Blvd		Analysis Agency ATTN: DRXSY-CM Aberdeen Proving Ground, MD 21005
12	Arlington, VA 22209 Defense Technical Info Ctr Cameron Station Alexandria, VA 22314	i	Director US Army Materiel Systems Analysis Agency ATTN: DRXSY-MP Aberdeen Proving Grounds, MD
	Department of the Army		21005
ţ	Commander, HQ TRADOC ATTN: ATEN-ME Fort Monroe, VA 23651	1	Director US Army Engineer Waterways Experiment Station ATTN: Chief, Library Branch Technical Info Ctr
1	HQDA (DAMA-AOA-M) Washington, DC 20310		Vicksburg, MS 39180
1	HQDA (DALO-TSM) Washington, DC 20310	1	Commander US Army Armament Research and Dev Command ATTN: DRDAR-TSS No. 59
1	HQDA (DAEN-RDL) Washington, DC 20314		Dover, NJ 07801
1	HQDA (DAEN-MPE-T) Washington, DC 20314	1	Commander US Army Troop Support & Aviation Materiel Readiness Com ATTN: DRSTS-MES (1)
1	Commander US Army Material Readiness Cmd ATTN: DRCDE-E 5001 Eisenhower Ave		4300 Goodfellow Blvd St Louis, MO 63120
1	Alexandria, VA 22333 Technical Library	2	Director Petrol & Fld Svc Dept US Army Quartermaster School Fort Lee, VA 23801
,	Chemical Systems Lab Aberdeen Proving Ground, MD 21010	2	HQ, 193d Infantry Brigade (Pan) ATTN: AFZU-FE APO Miami 34004

No. Copies	Addressee	No. Copies	Addressee
2	Special Forces Detachment,	1	Commander and Director
-	Europe		USA FESA
	ATTN: PBO		ATTN: FESA-TS
	APO New York 09050		Fort Belvoir, VA 22060
			Discussion
2	Engineer Representative	1	Director US Army TRADOC
	USA Research &		Systems Analysis Activity
	Standardization Group (Europe)		ATTN: ATAA-SL (Tech Lib)
	Box 65		White Sands Missile Range, NM
	FPO 09510		88002
1	Commander	1	HQ, USAEUR & Seventh Army
	Rock Island Arsenal	1	Deputy Chief of Staff, Engineer
	ATTN: SARRI-LPL		ATTN: ALAEN-MT-P
	Rock Island, IL 61201		APO New York 09403
	HQDA		
1	ODCSLOG	1	HQ, USAEUR & Seventh Army
	DALO-TSE		Deputy Chief of Staff, Operations
	Room 1E588		ATTN: AEAGC-FMD
	Pentagon, Washington, DC		APO New York, 09403
	20310		
	20310		MERADCOM
1	Plastics Technical Evaluation Ctr		Commander, DRDME-Z
	ARRADCOM, Bldg 3401	1	Technical Director, DRDME-ZT
	ATTN: A.M. Anzalone		Assoc Tech Dir/R&D, DRDME-ZN
	Dover, NJ 07801		Assoc Tech Dir/Red, Ditain Sir Assoc Tech Dir/Engrg & Acq.
1	Commandant		DRDME-ZE Spec Asst/Matl Asmt, DRDME-ZG
	US Army Engineer School		Spec Asst/Scs & Tech, DRDME-ZK
	ATTN: ATZA-CDD		
	Fort Belvoir, VA 22060		CIRCULATE
	_	1	Chief, Ctrmine Lab, DRDME-N
1	Commander	•	Chief, Engy & Wtr Res Lab, DRDME-G
	Headquarters, 39th Engineer		Chief, Elec Pw. Lab, DRDME-E
	Battalion (Cbt)		Chief, Camo & Topo Lab, DRDME-R
	Fort Devens, MA 01433		Chief, Mar & Br Lab, DRDME-M
			Chief, Mech & Constr Eqpt Lab.
1	President		DRDME-H
	US Army Armor and		Chief, Ctr Intrus Lab, DRDMF-X
	Engineer Board		Chief, Matl Tech Lab, DRDME-V
	ATTN: ATZK-AE-PD-E		Dir, Product A&T Directorate.
	Fort Knox, KY 40121		DRDME-T
			CIRCULATE

io. Copies	Addressee
2	Engy & Wtr Res Lab, DRDME-G
30	Pet & Envir Tech Div, DRDME-GS
3	Tech Reports Ofc, DRDME-WP
3	Security Ofc (for liaison officers), DRDME-S
2	Tech Library, DRDME-WC
i	Programs & Anal Dir, DRDME-U
1	Pub Affairs Ofc, DRDME-I
1	Ofe of Chief Counsel, DRDME-L
	Department of the Navy
1	Library (Code LO8A) Civil Engineering Lab Naval Construction Battalion Ctr Port Hueneme, CA 93043
	Department of the Air Force
ı	Chief, Lubrication Br Fuels & Lubrication Div ATTN: AFWAL/POSL Wright-Patterson AFB, OH 4543.
1	Department of Transportation Library, FOB 10A, M494-6 800 Independence Ave., SW Washington, DC 20591

